



STRIPPIT VX

UNSURPASSED PRODUCTIVITY

Strippit VX machines offer the most flexible turret configurations available.

A large turret capacity - 48 stations - enables the use of a standard turret load.

Large 88,9 mm auto-index stations accept indexable Multi-Tools to increase turret capacity. They provide indexing of any tool at any angle, which increases flexibility and productivity.

KEY FEATURES

High-speed processing

Flexible tool configuration

Expanded tool capacity using indexable Multi-Tools

Programmable, relocatable clamps

Full sheet utilisation

SPECIFICATIONS

	VX-1225	VX-1530
PUNCHING SPECIFICATIONS		
Max. punching capacity	200 kN	200 kN
Max. material thickness	6.35 mm	6.35 mm
Punching accuracy	± 0.1 mm	± 0.1 mm
Repetitive accuracy	± 0.05 mm	± 0.05 mm
MAX. HIT RATE ⁽¹⁾		
1 mm pitch	up to 920 HPM	up to 920 HPM
25.4 mm pitch	up to 530 HPM	up to 515 HPM
Marking	up to 1750 HPM	up to 1750 HPM
Feed clearance	25 mm	25 mm
Nominal work piece size	1250 x 2500 (4000) mm	1524 x 3048 (5000) mm
TABLE TYPE CAPACITIES		
Brush table ⁽²⁾	up to 150 kg	up to 150 kg
Work chute	450 x 500 mm	450 x 500 mm
Work clamps	3 CNC automatic, part pull out sensor	
TURRET - MAGAZINE		
Turret configuration	48 stations	48 stations
Auto-index stations	4 'D' - Ø 88.9 mm	4 'D' - Ø 88.9 mm
Max. tool capacity ⁽³⁾	76	76
Wheel Tool capacity	x	x
Tapping Tool capacity	x	x
Indexable Multi-Tool capacity	x	x
Angular positioning accuracy	± 0.05 degrees	± 0.05 degrees
Controller	Touch-P	Touch-P
Combined positioning speed X-Y	161 m/minute	130 m/minute
Tool change time	0.8 sec.	0.8 sec.
ELECTRICAL POWER		
Average power consumption	6.7 kW	6.7 kW
Standby operation	0.9 kW	0.9 kW
Lubrication system	x	x
AUTOMATION OPTIONS		
Automatic load/unload (PA)	x	x
Compact Tower (CT-P)	x	x
Bin sort	x	x
Robot pick/sort	x	x
Warehouse connectivity	x	x
Extended Tool Magazine (ETM)	x	x
Tool lubrication system	x	x

⁽¹⁾ material thickness + tip recess + die penetration ⁽²⁾ at reduced speed ⁽³⁾ with Multi-Tool

